

ADM X-Series Vertical Form Fill & Seal



Features

- Stainless Steel Construction
- Servo Motor Controlled Film Pull Belts
- Servo Motor Controlled Jaw Seal Actuation
- Panasonic Touch Screen Operator Interface
- Panasonic PLC - Based Control System
- Automatic Program Set-Up
- Instant Program Changeover
- Mark sensor (Fiber Optic) Registration Control
- Quick Change Former Assembly
- Product Clamp and Settler
- Full Safety Guarding and Interlocks (option)
- CE Approved Electrical

Optional Elements

- Polyethylene seal systems
- Material stopper
- Load shelf for heavy bag support
- Re-closable zipper
- Nitrogen gas flush systems
- Hole punch (Round or Euro)
- Vacuum assist units
- Static eliminators
- Gusseted device
- Special Power Requirement
- Special End-Seal Configurations

Model	ADM-X190	ADM-X240	ADM-X300
Bag Type	Pillow bag, gusseted bag	Pillow bag, gusseted bag	Pillow bag, gusseted bag
Bag Size	60-190(W) x Up to 230(L)	75-240(W) x Up to 300(L)	110-300(W) x Up to 380(L)
Speed	Max: 100 BPM (Single pull)		Max: 50 BPM (Double pull)
Power Supply	240V 50Hz 3.5kW	240V 50Hz 4.0kW	240V 50Hz 4.5kW
Air Pressure	0.2m ³ /min 0.6MPa	0.2m ³ /min 0.6MPa	0.2m ³ /min 0.6MPa
Machine Dim	1300X960X1150	1650x1300x1700	1680x1400x1850



ADM Packaging Automation P/L

3 Kerr Street, Preston, Vic, 3072, Australia

Ph: 03 9484 8791 Fax: 03 9484 7506

Email: info@admpa.com.au Website: www.admpa.com.au