

# ADM Bucket Elevator



## FEATURE

- Custom made to suit
- Standard spares supplied
- Polypropylene white litre buckets
- Easy access for cleaning
- Enclosed with clear or SS doors
- Stainless Steel structure for durability and sanitation
- Operating control panel
- Safety relay installed to AS4024
- Interface with vibratory feeder
- Power 0.75kW-2.5kW

## Option CIP Includes

- Jet Wash
- Air dry

Model	ADM-BE3F	ADM-BE3
Construction	Stainless Steel	Stainless Steel
Buckets	Polypropylene (white)	Polypropylene (white)
Flow rate (standard)	4.5m <sup>3</sup> /hr	4.5m <sup>3</sup> /hr
Bucket Sizes	1.3 litre@ 80% fill (380wide x 127pitch)	1.3 litre
Feeder	Included	Separate
Linear Speed (Std)	0.14m/s (60buckets/min)	0.14m/s
Power supply	240V 50Hz 0.75kW	240V 50Hz 0.75kW



Innovation in Flexible Packaging

## ADM Packaging Automation P/L

3 Kerr Street, Preston, Vic, 3072, Australia

Ph: 03 9484 8791 Fax: 03 9484 7506

Email: [info@admpa.com.au](mailto:info@admpa.com.au) Website: [www.admpa.com.au](http://www.admpa.com.au)